

BRAVA ACTRA JOY PLUS MULTIFUNCTION ARMREST

Ideal for wide-ranging applications in harsh environments: The BRAVA multifunction armrest guarantees a high level of flexibility when equipping industrial trucks, agricultural and construction machinery as well as in numerous industrial applications. It comprises an arm support and a control unit, which can be selected and configured to suit the application.

The newly developed module "ACTRA JOY" ensures a maximum of variability: It can be equipped with two joystick, a travel direction switch and with up to three auxiliary buttons. The high degree of functionality, excellent ergonomics and sensitive control ensurefatigue-free and precise work.

- · Ergonomically shaped armrest
- · Horizontal and vertical adjustment
- Stepless height adjustment supported by a gas strut
- · Customer-specific colours and symbols
- Communication via CANopen interface

Multifunction Armrests



Armrest with control unit ACTRA JOY



Height adjustment BRAVA



Armrest with control unit ACTRA JOY



| Technical data | | |
|------------------------------|------------------------------|--|
| Operation elements | | |
| Two-axis Finger Joystick | Contactless via Hall sensors | |
| Joystick limiter | Round, square, cross | |
| Joystick push button | Tactile switch | |
| Direction switch | Contactless via Hall sensors | |
| (momentary / latched) | | |
| Push button | Contactless via Hall sensors | |
| Momentary rocker switch with | Contactless via Hall sensors | |
| two positions | | |
| Momentary rocker switch with | Contactless via Hall sensors | |
| three positions | | |
| Latched rocker switch with | Contactless via Hall sensors | |
| two positions | | |
| Latched rocker switch with | Contactless via Hall sensors | |
| three positions | | |
| Electrical data | | |
| Voltage supply | 7 V – 65 V | |
| Nominal operating voltage | 12 V / 24 V / 48 V | |
| Transmission protocol | CANopen | |
| Cable and plug-in connector | Superseal 6 pin, 1.5 series | |
| | (injection-moulded on the | |
| | housing) | |
| Mechanical data | | |
| Dimensions | See drawings | |
| Mounting screws | 3 x Ø 9.0 mm | |
| Operating conditions | | |
| Operating temperature | -30°C to +65°C | |

| Order data | |
|---------------|-------------------------|
| Part-No. | Designation |
| 3108-00xxx-xx | ACTRAJOY |
| 3202-00563-00 | BRAVA arm support |
| 3202-00131-00 | BRAVA height adjustment |

Dimensions [mm]





