



VIARO KEY SWITCH

Due to its exclusive design and its technical functions, the VIAROkey switch serves as the ideal access control system for vehicles and machinery. The laser-cut (sidewinder) key blade harmonises perfectly with the design of the key bow and, furthermore, provides protection against manipulation.

The key bow can come in different colours and with customised logos. The VIAROkey switch is also available as an ignition switch.

- Laser-cut (sidewinder) key blade
- Two independent switch contacts
- Four 6.0 x 0.8 mm flat-blade terminals
- Current-carrying capacity: 16 ADC
- Either two or three key positions are possible (OFF – ON1 – ON2)
- Key can only be removed in the OFF position
- Different contact switching sequences possible
- Different closure types available
- Customized logos on the key bow possible
- Protection class: IP 54 (front)



Technical data	
Electrical data	
Rated operating voltage	12.0 VDC – 80.0 VDC
Ampacity	21 A
Switching current with cycle < 1 min.	16 A
Connection	Flat connector 6.3 x 0.8 mm
Operating conditions	
Ambient temperature	-40°C to +85°C
Service life	150,000 cycles
Degree of protection, front	IP 54
Degree of protection, connection-side	IP 00

Special versions	
<ul style="list-style-type: none"> • Customer-specific key grip possible • Colours can be customised 	

Order data	
Part No.	Designation
3106-00102NO2	2-stage, NO
3106-00104CO2	2-stage, changeover contact
3106-00105NO1	1-stage, NO

Switching sequence			
Position	3106- __ NO1	3106- __ CO2	3106- __
0	1 – 2 OFF 3 – 4 OFF	1 – 2 OFF 3 – 4 OFF	1 – 2 OFF 3 – 4 OFF
1	1 – 2 ON 3 – 4 ON	1 – 2 OFF 3 – 4 ON	1 – 2 ON 3 – 4 OFF
2	– –	1 – 2 ON 3 – 4 OFF	1 – 2 ON 3 – 4 ON

Dimensions [mm]

